

Hess Grade: 3/4 X 3/8 MN

ADDITIONAL GRADE SHARING THESE SPECS: 3/4 X 3/8

PARTICLE SIZE SPECIFICATION GRADE 3/4 X 3/8 MN			
MICRON	SIZE		ALLOWABLE PERCENT PASSING
	MM	U.S. MESH	
19000	19	3/4	95-100
9500	9.5	3/8	60-80
7920	7.92	5/16	40-70
4750	4.75	4	0-20
2380	2.38	8	0-18
300	0.3	50	0-15

TEST METHOD: ASTM C136-06

LOOSE BULK DENSITY GRADE 3/4 X 3/8 MN
46 lb/per cubic foot (dry) [736.8 kg/per cubic meter] (ASTM C29)



HP Grade three-quarter by three-eighths contains stones from 3/4-inches to 3/8-inches in size with some fines.

*MINE GRADES are crushed and screened at the mine and are not dried for packaging in palletted production bags, but rather available in bulk quantities.

GRADE APPLICATIONS

- Lightweight geotechnical fill (mine grade)
- Air filtration media
- Soilless grow media

PACKAGING OPTIONS

- 2 lb or 1 kg resealable bags
- 20 lb [9 kg] box
- 1800 lb [816 kg] super sacks (palletted)
- Bulk shipped in rail car or tractor trailer

ORDER

- Samples, small quantities: order direct from the PumiceStore.com
- Palletted super sacks, truckloads: contact us at sales@hesspumice.com or call 208-766-4777

PUMICE TECHNICAL DATA

Chemical analysis, physical properties, and other common data shared by all Hess Pumice grades are detailed on back.



(208) 766-4777 • www.hesspumice.com

Mining and refining the purest commercial deposit of white pumice on the planet.

Hess Pumice Technical Data

CHEMICAL ANALYSIS AND PHYSICAL PROPERTIES

Chemical Name: Amorphous Aluminum Silicate

TYPICAL ANALYSIS	GENERAL PROPERTIES
• Silicon Dioxide: 76.2%	• Appearance: White powder
• Aluminum Oxide: 13.5%	• Hardness (MOHS): 6
• Ferric Oxide: 1.1%	• pH: 7.2
• Ferrous Oxide: 0.1%	• Radioactivity: None
• Sodium Oxide: 1.6%	• Softening Point: 900 degrees C
• Potassium Oxide: 1.8%	• Water Soluble Substances: 0.15%
• Calcium Oxide: 0.8%	• Loss on Ignition - 5%
• Titanium Oxide: 0.2%	• GE Brightness: 84
• Magnesium Oxide: .05%	• Specific Gravity: 2.2
• Moisture: <1.0%	• Reactivity: Inert
• Crystalline SiO ₂ : None Detected	(except in the presence of calcium hydroxide or hydrofluoric acid)

DESCRIPTION

Amorphous (non-crystalline) in structure and composed primarily of aluminum silicate, pumice is a naturally calcined volcanic glass foam consisting of highly vesicular strands permeated with tiny air bubbles. It is these frothy, friable glass vesicles that, when carefully refined to various grades, give pumice its unique and infinitely useful qualities.

NOTES

- Chemical analysis and physical properties provided are common to all raw Hess pumice grades.
- **Grade Variety.** The natural, hard-yet-friable character of our pumice combined with our crushing and screening expertise allow us to offer pumice grades and grade blends down to 3 microns.
- **Safe to Use.** No hazardous crystalline structure: testing for crystalline silica (airborne particles of respirable size) finds no measurable Crystalline Silica (SiO₂) present. Free of heavy metals, pesticides, nano-particles, allergens. Certified organic input material.
- **Purity:** As the result of centuries of wave action from a now-extinct inland sea, our pumice is remarkably pure. Our mine grades are typically comprised of 98% pumice and 2% other igneous minerals, which are not removed through our mining processes.
- **Storage:** Keep dry and protected from the elements until use.



Pumice is a foamed glass stone naturally expanded by explosive volcanic eruption.